

**THERMAL TRANSFER REMOVABLE ADHESIVE  
SPEC# 01200**

**FACESTOCK**

**CALIPER** - 3.0mil  
**DESC.** - A bright white, ultra-smooth coated face offering high thermal transfer print quality for medium to high-speed printers. Ideal for barcode printing with or without ink coverage.  
**TENSILE** - **MD** 30# per inch width  
**CD** 18# per inch width  
**TEAR** - **MD** 44 grams  
**CD** 50 grams  
**STIFFNESS** – **MD** 105 mg  
**CD** 65 mg

**ADHESIVE**

**TYPE** - Emulsion Acrylic  
**MINIMUM APPLICATION TEMP** - +40F  
**SERVICE TEMP** - 0F to +175F  
**DESC.** - A standard removable with good initial tack and moderate long-term adhesion to many substrates. It may be repositionable on some substrates for up to 24 hours. Complies with FDA 175.105 for incidental food contact.

**LINER**

**CALIPER** - 2.5mil  
**DESC.** - 40# bleached super-calendered kraft stock featuring high internal strength, toughness and tear resistance.  
**TENSILE** - **MD** 38# per inch width  
**CD** 20# per inch width  
**TEAR** - **MD** 36 grams  
**CD** 41 grams

**SHELF LIFE** One year when stored at 72F at 50% RH.