

# TT MATTE SILVER POLYESTER PERMANENT ADHESIVE SPEC# 11101

## FACESTOCK

**CALIPER** - 2mil  
**DESC.** - A durable, high performance metallized face that offers excellent thermal stability and moisture resistance. This face stock is suitable for demanding applications such as nameplates and product ID labels. Specially print treated for receptivity with most film inks and thermal transfer printing systems.  
**TENSILE** - **MD** 23,000 psi  
**CD** 27,000 psi  
**TEAR** - **N/A**  
**STIFFNESS** - **N/A**

## ADHESIVE

**TYPE** - Emulsion Acrylic  
**MINIMUM APPLICATION TEMP** - +40F  
**SERVICE TEMP** - -20F to +300F  
**DESC.** - A general purpose clear acrylic that exhibits moderate initial tack, high shear with minimal cold flow and excellent die cutting properties.

## LINER

**CALIPER** - 3.2mil  
**DESC.** - 50# bleached, super-calendered paper promoting very good die cutting and matrix stripping characteristics.  
**TENSILE** - **MD** 45# per inch width  
**CD** 24# per inch width  
**TEAR** - **MD** 48 grams  
**CD** 58 grams

**SHELF LIFE** One year when stored at 72F at 50% RH.